

# Sentry Metered CDU

## C-30VD/VY Mixed Outlet 3-Phase 50/60A

### Key Features

- > **Input Current Monitor:**  
Precisely measure the aggregate current draw (in amps) on each phase of the power circuit. On-site verification of the input current with the LED digital display.
- > **Power Distribution:** 208V, 3-Phase, 50- and 60-Amp Power Input
- > **High-Density Power Distribution:** (24) IEC 60320 C13 and (6) IEC 60320 C19 outlets
- > **Branch Circuit Protection:**  
Sentry CDUs meet UL 60950-1 requirements
- > **Vertical Mounting:** Zero-U button and bracket mounting options

### High Density Metered Power Distribution

Increasing power demands and density in the equipment cabinet requires new functionality from your cabinet PDU. The Sentry CDU product family uniquely meets these demands.

The Sentry Cabinet Power Distribution Unit (CDU) is an intelligent PDU with local LED input current monitoring, allowing network engineers to utilize the CDU's True RMS Power Monitor to precisely measure the current (in amps) that network devices are drawing on the power circuit. As new servers and devices are added to the power drop, immediately observe its impact on the cumulative current draw. This allows the engineer to safely load each circuit to its maximum allowable load capacity without the danger of overloading the power circuit.

### Additional Benefits:




#### Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections  
> UL-489 rated circuit breakers



#### Input Current Monitoring

The CDU's exclusive Digital True RMS current monitoring is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase.



#### Button Mounting

All CDUs are also compatible with button & "keyhole" style mounting for cabinets. Several cabinet manufacturers are now using this method for installing power distribution units in the cabinet.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
C-30VDX411C2-002	240V, 3-phase Delta, 50/60Hz	60A	IEC Blue 9hr 3P+G Plug, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13 (6) IEC 60320/C19	72.0 x 1.75 x 3.50 in. (1829 x 44 x 89 mm)
C-30VDV411C2-002	240V, 3-phase Delta, 50/60Hz	50A	CS8365C Plug, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13 (6) IEC 60320/C19	72.0 x 1.75 x 3.50 in. (1829 x 44 x 89 mm)
C-30VYY411C2-002	208V, 3-phase Wye, 50/60Hz	60A	IEC Blue 9hr 3P+N+G Plug, 10'(3m), Bottom/Frt Cord	(24) IEC 60320/C13 (6) IEC 60320/C19	72.0 x 1.75 x 3.50 in. (1829 x 44 x 89 mm)

## Additional Specifications

### Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > FCC Class A, Part 15
- > CE
- > EMC - EN 55022 Class A, EN 55024, CISPR 22 Class A

### Branch Circuit Protection

- > Compliant to UL 60950-1



## Server Technology

### HEADQUARTERS - NORTH AMERICA

Server Technology, Inc.  
1040 Sandhill Drive  
Reno, NV 89521  
United States  
1.775.284.2000 Tel  
1.775.284.2065 Fax  
sales@servertech.com  
www.servertech.com  
www.servertechblog.com

### EMEA

Server Technology Intl  
Sienna Court  
The Broadway  
Maidenhead  
Berkshire  
SL6 1NJ  
United Kingdom  
+44 (0) 1628 509053 Tel  
+44 (0) 1628 509100 Fax  
salesint@servertech.com

### APAC

Server Technology Intl  
37th Floor, Singapore Land Tower  
50 Raffles Place  
Singapore 048623  
+65 (0) 6829 7008 Tel  
+65 (0) 6234 4574 Fax  
salesint@servertech.com