

# LED Displays VS. LCD Displays

## Overview

The type of onboard current display built into your Intelligent Cabinet Power Distribution Unit (CDU) isn't typically a top priority when choosing the right CDU for your cabinet, however, there are a few important specifications that should be considered when evaluating various makes and models of CDUs. Below is a comparison chart that shows you the difference between LED displays and LCD displays. Due to the LED's resilience, longevity, brightness and other factors, Server Technology believes that the pros of the LED display vastly outweigh the specs of the LCD display.



	LED Display	LCD Display
<b>Operating Temperature</b>	-40 to 85C	Commercial Grade Typically 0 to 50C Industrial Grade Typically -20 to 70C
<b>Storage Temperature</b>	-40 to 100C	Commercial Grade Typically -10 to 50C Industrial Grade Typically -30 to 85C
<b>Longevity</b>	100000 hours typical	50000 hours on crystal. Backlight life can be less dependant on technology used.
<b>Brightness</b>	Viewing distance up to 23' (7m)	Requires backlight to be continuously on. With backlight typically 10' (3m)
<b>Viewing angle</b>	60 degrees	Typical LCD is 45 degrees. High contrast models can get to 60 degree viewing angle
<b>Other considerations</b>	Server Technology has specified high intensity, low current draw LEDs for CDU applications.	LCDs can distort due to pressure on the display and thus require an additional protective window. Backlight lifespan can vary. 2500 Hours with Electroluminescence LED technology must be used to increase backlight life

## Summary

Current monitoring is critical to preventing overloaded circuits in data centers, simple load balancing, and it also helps data center personnel utilize the available power. All Server Technology CDUs with onboard current monitoring use LED digital displays on the CDU enclosure to report the input current (in Amps) of each phase or branch circuit. Over 25 years of data center power distribution research has shown us that this method has the most benefits when it comes to displaying power readings locally.



HEADQUARTERS - NORTH AMERICA  
1.775.284.2000 Tel  
1.775.284.2065 Fax  
sales@servertech.com  
www.servertech.com

EMEA  
Server Technology Intl  
+44 (0) 1628 509053 Tel  
+44 (0) 1628 509100 Fax  
salesint@servertech.com

APAC  
Server Technology Intl  
+65 (0) 6829 7008 Tel  
+65 (0) 6234 4574 Fax  
salesint@servertech.com